

SERIE EL2

Rad

Reifen aus Elastik-Vollgummi schwarz, unlöslich aufvulkanisiert, geringer Rollwiderstand.

Radkörper aus Aluminium mit Rillenkugellager.

Reifen-Härte 70° +/-5° Shore A

Temperaturbereich -30°C bis +80°C



	(mm)	(mm)	(mm)	(mm)	(kg)
EL2/080K	80	38	12	40	120
EL2/100K	100	40	15	40	180
EL2/125K	125	40	20	50	250
EL2/125K/2	125	50	20	50	270
EL2/125K/3	125	50	20	60	270
EL2/160K	160	50	20	60	350
EL2/200K	200	50	20	60	450
EL2/200K/2	200	50	25	60	450
EL2/250K	250	50	20	60	550
EL2/250K/2	250	50	25	60	550
EL2/300K	300	60	30	60	650

Gehäuse

Stahlblechgehäuse glanzverzinkt,

Schwenklager mit zweifachem Kugelkranz,

Radachse verschraubt



Lenkrolle	Lenkrolle mit Totalfeststeller	Bockrolle									Lagerung
			(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)	
EL2/L080K	EL2/L080K/TF	EL2/B080K	80	38	105	45	105x85	80x60	9	120	
EL2/L100K	EL2/L100K/TF	EL2/B100K	100	40	128	45	105x85	80x60	9	180	
EL2/L125K	EL2/L125K/TF	EL2/B125K	125	40	155	45	135x110	105x80	11	250	
EL2/L160K	EL2/L160K/TF	EL2/B160K	160	50	195	52	135x110	105x80	12	350	
EL2/L200K	EL2/L200K/TF	EL2/B200K	200	50	235	55	135x110	105x80	12	400	
EL2/L250K	EL2/L250K/TF	EL2/B250K	250	50	290	66	135x110	105x80	11	550	



Lieferbare Variante: mit blau-grauem Reifen (spurlos)