






SERIE PU2

Rad

Laufbelag aus hochwertigem Polyurethan, fest aufgegossen, elastisch, abriebfest, geringer Rollwiderstand und geräuscharmer Lauf.
Radkörper aus Aluminium mit Rillenkugellager.

Reifen-Härte 92° +/-2° Shore A
Temperaturbereich -30°C bis +80°C











						
	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
PU2/080K	80	30	12	40		175
PU2/100K	100	30	15	30		200
PU2/100K/2	100	40	12	40		280
PU2/125K	125	30	15	30		250
PU2/125K/2	125	40	20	50		350
PU2/125K/3	125	50	20	60		400
PU2/150K	150	40	20	40		450
PU2/150K/2	150	50	20	60		500
PU2/160K	160	50	20	60		600
PU2/180K	180	50	20	60		700
PU2/200K	200	50	20	60		800
PU2/200K/2	200	50	25	60		800
PU2/250K	250	60	25	60		1000
PU2/250K/2	250	60	30	60		1000

Gehäuse

Stahlblechgehäuse glanzverzinkt,
Schwenklager mit zweifachem Kugellager,
Radachse verschraubt



											
Lenkrolle	Lenkrolle mit Totalfeststeller	Bockrolle	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)	Lagerung
PU2/L080K	PU2/L080K/TF	PU2/B080K	80	30	105	45	105x85	80x60	9	150	
PU2/L100K	PU2/L100K/TF	PU2/B100K	100	30	128	45	105x85	80x60	9	200	
PU2/L125K	PU2/L125K/TF	PU2/B125K	125	30	155	45	135x110	105x80	11	250	
PU2/L160K	PU2/L160K/TF	PU2/B160K	160	50	195	52	135x110	105x80	12	400	
PU2/L200K	PU2/L200K/TF	PU2/B200K	200	50	235	55	135x110	105x80	12	400	
PU2/L250K	PU2/L250K/TF		256	60	290	70	175x175	140x140	14	600	